

EACO MIG 200 COMPACT WORKSHOP

MIG/
MMA

PORTABLE INVERTER MIG & STICK WELDER

PART # MIGMMA200CW

Features

The MIG 200CW is a medium duty single phase inverter multi-process MIG and MMA (Stick) welding machine. Its advanced inverter design requires less energy compared to traditional stepped transformer machines. Suitable for Steel, Stainless Steel, Aluminium and more. Optional spool gun ready.

- “End of arc program” to remove ball on end of wire
- Spatter control for optimum arc adjustment
- Adjustable burn back control to set wire stick-out
- Dual welding parameters with Crater Fill feature. Ideal for increased productivity and multi positional welding
- Soft start feature for perfect starts
- 3 Year Warranty



What's Included:

- EACO 200A MIG/STICK INVERTER WELDING MACHINE
- TBi 250, 200A @ 35% x 4M WELDING TORCH
- WILSON Arg or CO₂ REGULATOR & 2m GAS HOSE
- 4m EARTH GROUND CABLE & CLAMP
- 15A ELECTRICAL PLUG, 3.2m INPUT LEAD
- REMOVABLE HEAVY DUTY TROLLEY w/ GAS BOTTLE TRAY
- ELECTRICAL SAFETY TEST TAG



45 Angle St.
Onehunga, Auckland 1061

09 636 0916
sales@weldit.co.nz

EACO MIG 200 COMPACT WORKSHOP

MIG/
MMA

PORTABLE INVERTER MIG & STICK WELDER

PART # MIGMMA200CW



FEATURE	FUNCTION / BENEFIT
WORKING INDICATOR	POWER ON/OFF
OVERLOAD INDICATOR	THERMAL OVERLOAD INDICATOR
CRATER CURRENT	CRATER AMPERAGE (CRATER WIRE FEED SPEED) ADJUST
CRATER VOLTAGE	CRATER VOLTAGE ADJUST
MMA CURRENT	MMA AMPERAGE ADJUSTMENT
SPATTER CONTROL	FINE TUNE ADJUSTMENT TO CONTROL SPATTER (INDUCTANCE)
MIG WELDING CURRENT	MIG/FCAW WELDING AMPERAGE SELECTOR
MIG WELDING VOLTAGE	MIG/FCAW VOLTAGE SELECTOR
MIG/MMA	PROCESS SELECTION SWITCH
2T/4T	MOMENTARY OR LATCHING TRIGGER MODE SELECTION
CRATER ON/OFF	ON/OFF CRATER FUNCTION, DUAL PARAMETER SWITCH
GAS CHECK	GAS PURGE

POWER SOURCE SPECIFICATIONS	
INPUT POWER	230V 1ph
DUTY CYCLE	200A @ 60%
OUTPUT CURRENT RANGE	30 - 200A
OUTPUT VOLTAGE RANGE	15.5 - 26V
MAX CURRENT (Imax)	24.5A
EFFECTIVE CURRENT (Ieff)	19.0A
WIRE FEEDER SPECIFICATIONS	
DUTY CYCLE	350A @ 100%
WIRE DIAMETERS	0.6 - 1.6mm
SPEED RANGE	2.0 - 18 m/min
RATED CURRENT	3.5A
RATED VOLTAGE	24V
PACKAGE SPECIFICATIONS	
DIMENSION (mm)	860 X 290 X 700
WEIGHT	43.5kg



45 Angle St.
Onehunga, Auckland 1061

09 636 0916
sales@weldit.co.nz